

GAOKEview Specification of Infrared whiteboard

Hangzhou Gaoke Industry & Trade Co., Ltd.

1. Product Features



- * Multi-touch, interactive experience;
- * Strong surface corrosion resistance, scratch resistance;
- * Free drive, HID technology, plug and play;
- * High respond speed, accurate positioning;
- * Nano-coated panel;
- * A variety of gesture recognition, user-friendly operation.

2. Specification

Model	GK-880H/83S	GK-880H/94S	GK-880H/100S	GK-880H/130S	GK-880H/150S
Induction way	Infrared induction				
Size	83 inch	94 inch	100inch	130inch	150 inch
Aspect ratio	4:3	16:10	16:9	16:6	16:6
Shortcut key	Dual Sides	Dual Sides	Dual Sides	Dual Sides	Dual Sides
Working area (mm)	1660×1165	1987 ×1165	2151×1165	2987×1090	3467×1270
Projection size (mm)	1560×1165	1855×1165	2059×1165	2887×1090	3367×1270
Product size (mm)	1725×1230×40	2052 ×1230×40	2216×1230×40	3052×1155×40	3532×1335×40
Package size (mm)	1836 ×1338×100	2163 ×1338×100	2327×1338×100	3163 ×1263 ×100	3643×1443 ×100
N.G./G.W.	15 /22 ±2.0Kg	18/25 ±2.0Kg	19 /27 ±2.0Kg	25 /35 ±2.0Kg	32 /46 ±2.0Kg

3. Technical specification

Writing ways	Touch, no need for a special pen, any opaque and blunt objects such as fingers and pen pointer can realize writing and operating.		
Screen material	Using macromolecule anti-glare panel material and optimized for projection	Precision	< 1mm
Back plate material	Metal plate material	Resolution	32768×32768
Frame material	Aluminum	Power supply	Only USB
Anti-light intensity	Support working under sunlight	Consumption	<1W
Modular design	PCB can be directly pulled out, easy maintenance	Driver mode	Free driver,plug and play
Connecting	USB cable	Working temperatures	-15-55℃
Supported OS	Win10/Win8/Win7/Vista/XP/2003/2000/Me/98/Linux/Mac OX	Working humidity	10%-95%
Cursor speed	250 points/Sec	Mark pen	Support
Installation	Wall mounted or mobile stand(Optional)	USB cable length	5m