

GAOKEview Capacitive Floor Standing Digital Signage-T982

Product Features



- **Appearance:** Industrial-grade structural design concept, one body molding frame, thin and beautiful body, simple installation and convenient maintenance, unique heat dissipation technology, can support 7*24 hours of work
- **High-definition:** Using IPS high-definition LCD panel, colorful, high brightness, up to 2160P video, picture decoding and playback, can achieve high-quality picture output display
- **Intelligence:** Equipped with smart Android operating system, pre-installed front-end information publishing software, powerful functions, and supports third-party software installation, which can meet diversified usage needs

- **Touch:** High-channel capacitive G+FF touch solution, accurate touch, smooth writing, fast response, strong anti-interference, can support up to 20 points of touch
- **High-end:** Widely used in government and enterprise, medical care, finance, education, transportation, supermarkets, multimedia exhibition halls and other scenes that require touch query and intelligent interaction ,It is an intelligent high-end touch all-in-one machine

Display Parameter				
LCD Grade	New A+ LCD display panel			
Size	43inch	50inch	55inch	65inch
Backlight Type	E-LED	E-LED	E-LED	E-LED
Resolution(pixels)	2160*3840	2160*3840	2160*3840	2160*3840
Aspect ratio	9:16	9:16	9:16	9:16
Brightness	350cd/m2(typ.)	350cd/m2(typ.)	350cd/m2(typ.)	350cd/m2(typ.)
Refreshing Frequency	60Hz	60Hz	60Hz	60Hz
Viewing Angle	178°(H) / 178°(V)	178°(H) / 178°(V)	178°(H) / 178°(V)	178°(H) / 178°(V)
Life Time	50,000 Hours (min.)	50,000 Hours (min.)	50,000 Hours (min.)	50,000 Hours (min.)
View Area (mm)	529.25(H)x940.89(V) mm	616.41(H)x1095.84(V) mm	680.4(H)x1209.6(V) mm	803.52(H)x1428.48(V) mm
Surface Treatment	Foggy surface (Haze1%)			
Display Colors	16.7M(8bit)	16.7M(8bit)	16.7M(8bit)	16.7M(8bit)

System Configuration	
Operating System	Android
CPU	T982 Quad-core Cortex-A55 Max 1.9GHz
GPU	Mali -G52
RAM	4GB
ROM	32GB
Android Version	Android 14
Input interfaces	USB3.0 *1, USB OTG*1, TF Slot*1,LAN*1,DC-12V-IN HDMI*1
Audio Interface	3.5mm dual-channel audio interface*1
Network	Supports RJ45 R/A 100Mbps Ethernet; 2.4GHz + 5GHz dual-band Wi-Fi 6; Supports Wi-Fi 802.11 a/b/g/n/ac/ax protocols; Bluetooth 5.3; Supports external 4G and 5G modules.
System Upgrade	Supports OTA remote upgrade, USB Flash disk upgrade

System functions	
Software support	Supporting installation of third-party application software
WIFI-Hotspot	Support WIFI-Hotspot
Start-up method	Power on start
System Authority	Open the root privileges for customized software development
Remote monitoring	Real-time remote monitoring, self-recovery from system crashes, 24/7 unattended operation.
Play mode	Supports switching between server and standalone modes.
Language	Support Chinese, Traditional Chinese, English and other languages
Memory expansion	Support up to 256G TF card expansion
Customization	Customizable boot LOGO
Audio function	2-channel output (8 Ω /5W dual audio amplifier output)
Mouse and Keyboard Functions	Standard Android keyboard, third-party input methods(optional)
USB function	Updating/Playing Media Files/External Devices

Touch Parameter		
Touch Parameter	Touch Type	Projected Capacitive Technology
	Touch scheme	Capacitance G+FF
	Touch resolution	16384*16384
	Touch life	>50 million times
	Touch points	10-point touch
	Response Time	$\leq 5\text{ms}$
	Touch Accuracy	$\leq 2\text{mm}$
	Input Mode	Fingers or capacitive styluses
	Data Output method	Coordinate output
	Touch interface	USB
	Drive mode	Free drive
	Calibration method	Manufacturer-specific software calibration

Structure Parameter				
Size	43inch	50inch	55inch	65inch
Color	Silver/Black	Silver/Black	Silver/Black	Silver/Black
Border Material	Aluminum profile (oxidized wire drawing)			
Body material	Metal cold-rolled steel sheet (metal spraying)			
Surface Material	3mm tempered glass (physical tempering)			
Product Size	1733.8*578.45*450mm (including base)	1733.8*665.61*450mm (including base)	1873*729.6*450mm (including base)	1983*852.72*450mm (including base)
Package Size	1750*155*755mm	1775*155*755mm	1955*173*870mm	2015*173*984mm
Net weight/Gross weight	32KG/37.5KG	35KG/40.4KG	40KG/48KG	50KG/58KG
Installation method	Floor standing			

Electrical performance	
Applicable scene	Indoor
Rated voltage	AC110-220V
Standby power	≤1W
Rated power	43" ≤65W 50" ≤95W 55" ≤130W 65" ≤150W
Use environment	Temperature-0℃~55℃/humidity 10%RH~90%RH
Storage environment	Temperature - 5℃~60℃/humidity 10%RH~90%RH

Packing List	
Machine	x1
Power Cord	x1
WiFi antenna	x1
Warranty card/Certificate of qualification	x1
Hex wrench	x1
Base screw	x1 Set