

GAOKEview Interactive Flat Panel

Technical Specification-U2-9679



Version	Description	Date	Fiction
V1.0		2025.11.25	

Product Features

- With 4K UHD display, supporting full-channel 4K UI display
- Zero-bonding technology, 3.22mm anti-glare tempered glass with high haze OC, anti-ambient light interference, clearer display
- Built-in eye protection and auto-brightness sensor
- ±2mm high precision infrared touch, smooth writing
- Supports two-pen writing at the same time and two-colors display, making it easier for multiple people to collaborate
- The default front port supports USB3.0*1+USB2.0*1+TYPE-C+TOUCH USB+HDMI IN
- Smart sidebar menu. Built-in touch lock.
- Support multi-task windows
- Support built-in 13MP/48MP Camera&8 Array MIC (Optional)

Display Parameter

Size	55inch	65inch	75inch (Low/High Power)	86inch
Backlight Type	DLED	DLED	DLED	DLED
Panel Brand	BOE/CSOT	BOE/CSOT	BOE/CSOT	BOE/CSOT
Resolution(pixels)	3840x2160	3840x2160	3840x2160	3840x2160
Brightness	≥350cd/m2(typ.)	≥350cd/m2(typ.)	≥350cd/m2(typ.)	≥350cd/m2(typ.)
Aspect Ratio	16:9	16:9	16:9	16:9
Contrast Ratio	5000:1	5000:1	1200:1	5000:1
Response Time	6ms (typ.)	6ms (typ.)	6ms (typ.)	6ms (typ.)
Pixel Pitch (mm)	0.105(H)x 0.315(V)	0.1433(H) x 0.4298(V)	0.315(H) x 0.315(V)	0.1433(H) x 0.4298(V)
Refreshing Frequency	60Hz	60Hz	60Hz	60Hz
Viewing Angle	178°(H)/178°(V)	178°(H)/178°(V)	178°(H)/178°(V)	178°(H)/178°(V)
Life Time	100000 Hrs	100000 Hrs	100000 Hrs	100000 Hrs
View Area (mm)	1209.6×680.4(mm)	1428.48×803.52(mm)	1650.24×928.26(mm)	1872×1053(mm)